



- Frame : Thermoplastic Aluminum alloy  
外框材質：環保防火 鋁合金
- Impeller : Thermoplastic PBT UL94-V0  
扇葉材質：環保防火PBT
- Bearing System : Sleeve Bearing/WRB Bearing/Two Ball Bearing  
軸承結構：※含油軸承/★專利軸承/◎滾珠軸承
- Unit Weight : 26g  
風扇單體重量：26克

Model No.	Bearing Type	Voltage (VDC)	Current (A)	Power (W)	Speed (RPM)	Air Flow (CFM)	Air Flow (m <sup>3</sup> /min)	Air Pressure (mmH <sub>2</sub> O)	Air Pressure (Inch H <sub>2</sub> O)	Noise (dBA)
TRS6010x05L	※★◎	5 (3.5~6.8)	0.07	0.35	3000	12.00	0.36	2.10	0.09	19.0
TRS6010x05M	※★◎	5 (3.5~6.8)	0.15	0.75	4000	16.00	0.48	2.80	0.10	26.4
TRS6010x05H	※★◎	5 (3.5~6.8)	0.23	1.15	5000	20.00	0.60	3.50	0.15	33.0
TRS6010x12L	※★◎	12 (6.0~13.5)	0.03	0.36	3000	12.00	0.36	2.10	0.09	19.0
TRS6010x12M	※★◎	12 (6.0~13.5)	0.05	0.60	4000	16.00	0.48	2.80	0.10	26.4
TRS6010x12H	※★◎	12 (6.0~13.5)	0.10	1.20	5000	20.00	0.60	3.50	0.15	33.0
TRS6010x24L	※★◎	24 (18.0~26.5)	0.03	0.72	3000	12.00	0.36	2.10	0.09	19.0
TRS6010x24M	※★◎	24 (18.0~26.5)	0.04	0.96	4000	16.00	0.48	2.80	0.10	26.4
TRS6010x24H	※★◎	24 (18.0~26.5)	0.08	1.92	5000	20.00	0.60	3.50	0.15	33.0

★產品詳細數據及功能請參閱承認書 Product have a detail in the approval sheet.  
★產品規格變更不另行通知 Specifications are subject to change without notice.