



- Frame : Thermoplastic Aluminum alloy
外框材質：環保防火 鋁合金
- Impeller : Thermoplastic PBT UL94-V0
扇葉材質：環保防火PBT
- Bearing System : Sleeve Bearing/WRB Bearing/Two Ball Bearing
軸承結構：※含油軸承/★專利軸承/◎滾珠軸承
- Unit Weight : 28g
風扇單體重量：28克

Model No.	Bearing Type	Voltage (VDC)	Current (A)	Power (W)	Speed (RPM)	Air Flow (CFM)	Air Flow (m ³ /min)	Air Pressure (mmH ₂ O)	Air Pressure (Inch H ₂ O)	Noise (dBA)
TRS7010x05L	※★◎	5 (3.5~6.8)	0.21	1.05	2000	10.31	0.29	0.90	0.03	23.4
TRS7010x05M	※★◎	5 (3.5~6.8)	0.26	1.30	2500	14.71	0.42	1.55	0.06	27.2
TRS7010x12L	※★◎	12 (6.0~13.5)	0.15	1.80	2000	10.31	0.29	0.90	0.03	23.4
TRS7010x12M	※★◎	12 (6.0~13.5)	0.19	2.28	2500	14.71	0.42	1.55	0.06	27.2
TRS7010x12H	※★◎	12 (6.0~13.5)	0.26	3.12	3000	18.46	0.52	2.07	0.08	30.9
TRS7010x24L	※★◎	24 (18.0~26.5)	0.08	1.92	2000	10.31	0.29	0.90	0.03	23.4
TRS7010x24M	※★◎	24 (18.0~26.5)	0.12	2.88	2500	14.71	0.42	1.55	0.06	27.2
TRS7010x24H	※★◎	24 (18.0~26.5)	0.16	3.84	3000	18.46	0.52	2.07	0.08	30.9

★產品詳細數據及功能請參閱承認書 Product have a detail in the approval sheet.
★產品規格變更不另行通知 Specifications are subject to change without notice.

⊗ Bearing System ※ : Sleeve ★ : WRB Bearing ◎ : Ball