



- Frame : Thermoplastic Aluminum alloy
外框材質：環保防火 鋁合金
- Impeller : Thermoplastic PBT UL94-V0
扇葉材質：環保防火PBT
- Bearing System : Sleeve Bearing/WRB Bearing/Two Ball Bearing
軸承結構：※含油軸承/★專利軸承/◎滾珠軸承
- Unit Weight : 40g
風扇單體重量：40克

Model No.	Bearing Type	Voltage (VDC)	Current (A)	Power (W)	Speed (RPM)	Air Flow (CFM)	Air Flow (m ³ /min)	Air Pressure (mmH ₂ O)	Air Pressure (Inch H ₂ O)	Noise (dBA)
TRS8010x05L	※★◎	5 (3.5~6.8)	0.21	1.05	2500	18.11	0.51	1.29	0.05	26.4
TRS8010x12L	※★◎	12 (6.0~13.5)	0.15	1.80	2500	18.11	0.51	1.29	0.05	26.4
TRS8010x12M	※★◎	12 (6.0~13.5)	0.19	2.28	3000	21.71	0.61	1.81	0.07	30.2
TRS8010x12H	※★◎	12 (6.0~13.5)	0.25	3.00	3300	23.81	0.67	2.40	0.08	32.4
TRS8010x24L	※★◎	24 (18.0~26.5)	0.08	1.92	2500	18.11	0.51	1.29	0.05	26.4
TRS8010x24M	※★◎	24 (18.0~26.5)	0.13	3.12	3000	21.71	0.61	1.81	0.07	30.2
TRS8010x24H	※★◎	24 (18.0~26.5)	0.16	3.84	3300	23.81	0.67	2.40	0.08	32.4

★產品詳細數據及功能請參閱承認書 Product have a detail in the approval sheet.
★產品規格變更不另行通知 Specifications are subject to change without notice.

⊗ Bearing System ※ : Sleeve ★ : WRB Bearing ◎ : Ball