



- Frame : Thermoplastic Aluminum alloy  
外框材質：環保防火 鋁合金
- Impeller : Thermoplastic PBT UL94-V0  
扇葉材質：環保防火PBT
- Bearing System : Sleeve Bearing/WRB Bearing/Two Ball Bearing  
軸承結構：※含油軸承/★專利軸承/◎滾珠軸承
- Unit Weight : 120g  
風扇單體重量：120克

Model No.	Bearing Type	Voltage (VDC)	Current (A)	Power (W)	Speed (RPM)	Air Flow		Air Pressure		Noise (dBA)
						(CFM)	(m <sup>3</sup> /min)	(mmH <sub>2</sub> O)	(Inch H <sub>2</sub> O)	
TRS9225x12L	※★◎	12 (3.5~6.8)	0.11	1.32	2100	43.80	1.24	2.19	0.86	29.8
TRS9225x12M	※★◎	12 (3.5~6.8)	0.17	2.04	2800	57.13	1.61	3.73	1.47	34.2
TRS9225x12H	※★◎	12 (6.0~13.5)	0.28	3.36	3500	70.46	1.90	5.67	2.23	40.3
TRS9225x12VH	※★◎	12 (6.0~13.5)	0.40	4.80	4200	83.80	2.37	8.03	3.16	44.9
TRS9225x24L	※★◎	24 (6.0~13.5)	0.06	1.44	2100	43.80	1.24	2.19	0.86	29.8
TRS9225x24M	※★◎	24 (18.0~26.5)	0.08	1.92	2800	57.13	1.61	3.73	1.47	34.2
TRSV225x24H	※★◎	24 (18.0~26.5)	0.14	3.36	3500	70.46	1.99	5.67	2.23	40.3
TRS9225x24VH	※★◎	24 (18.0~26.5)	0.20	4.80	4200	83.80	2.37	8.03	3.16	44.9

★產品詳細數據及功能請參閱承認書 Product have a detail in the approval sheet.  
★產品規格變更不另行通知 Specifications are subject to change without notice.

⊗ Bearing System ※ : Sleeve ★ : WRB Bearing ◎ : Ball